
DiagnostX MX-3000 Master Device Information Sheet

Extend the DiagnostX Coverage of Your Radio System



The MX-3000 DiagnostX Master device utilizes robust, redundant hardware with higher performance processors to accommodate the requirements of larger, geographically dispersed systems. The DX-2002 analyzer accepts up to three (3) NX-200 remote receivers connecting simultaneously (depending on available WAN bandwidth). Larger systems will require the more powerful MX-3000. The MX-3000 Master device does not function as receiver; it receives data from the remote NX-200 devices and combine the results in a single view in the DiagnostX Viewer (DV) console.

The MX-3000 DiagnostX network using the NX-200 series of remote receivers is ideal for larger county-wide systems as well as state and regional systems. In the past, many agencies have moved their DiagnostX device periodically from site to site in order to cover their entire system. Others have combined multiple DiagnostX devices in a networked configuration to ensure continuous system-wide coverage in a unified database. It is now possible to use the MX-3000 with the smaller, more economical NX-200 remote receivers to achieve the same result.

All the data is forwarded across an IP network back to the MX-3000 device, and presented in a single consolidated view. The data transfer rate is only 13 KB per transmission sent.

Contact LocusUSA for a quote at 321.727.3077 or sales@locususa.com.

Patent Nos.

United States: 8565096, 8948022, 9282482, 8600371, 8825042, 9432866 & 9681321B2 • Canadian: 2746238 • Australian: 2010235881, 2012253596 & 2015203442
Other Patents Pending.

LocusUSA and DiagnostX are registered trademarks of Locus Location Systems, LLC. All rights reserved.